

**Tomographic imaging using penetrating radiation**

Patent Number: EP1004272  
Publication date: 2000-05-31  
Inventor(s): GRIESMER JEROME J (US); NEGRELLI DONALD E (US); LIN ZHONGMIN (US);  
PLUT LEONARD F (US)  
Applicant(s): PICKER INT INC (US)  
Requested Patent: ☐ EP1004272  
Application  
Number: EP19990308788 19991104  
Priority Number  
(s): US19980200652 19981125  
IPC Classification: A61B6/02  
EC Classification: A61B6/02J  
Equivalents: ☐ JP2000157525, ☐ US6236708  
Cited Documents: EP0106402; GB2062403; GB2046468; GB2063509; DE2746035

**Abstract**

A penetrating radiation source (14) is disposed on one side of an object (10) which is on an object support (12). A flat panel radiation detector (18) is stationarily disposed on the opposite side of the object (10) than the source (14). A moving system (16) moves the source (14) with respect to the object (10). In each position (Xi, Yi, Zi) of the source (14) a centre ray of the x-ray beam strikes the detector (18) at a corresponding location (xi, yi, 0). For each position (Xi, Yi, Zi) of the source (14), the image (xi, yi, 0) of an object located on a focal plane offsets by a vector displacement (Di) relative to a reference position (xo, yo, zo) of the image when the source is at (X0, Y0, Z0). A processor (28) shifts and interpolates each view by the different vector displacements corresponding to each of the focal planes (L1, L2,...) and integrates the images to generate a series of slice image representations which are stored in a volume image memory (30). In this manner, by adjusting the view offset by an amount corresponding to each of the focal planes,

(L1, L2, ...) the same data set is used to generate all of the slices of the resultant volume image. 

Data supplied from the esp@cenet database - I2